Data sheet

valid from: 4/5/26





TP Fixed flange PVC-U metric

- **DN** indicates the nominal diameter of the PVC pipe
Bolt holes PN10
- Maximum medium- or ambient temperature 45°

d (mm)	d (inch)	DN (mm)	PN (bar)	Code	SP	GP	Weight (kg)	L (mm)	S (mm)	f (mm)	E (mm)	l (mm)	Z (mm)
20		15	10	**RV0FFI200**	100		0.077	16	11	14	95	65	4.5
25		20	10	**RV0FFI250**	70		0.103	19	12	14	105	75	4.5
32		25	10	**RV0FFI320**	120		0.142	22	14	14	115	85	4.5
40		32	10	**RV0FFI400**	60		0.223	26	15	18	140	100	4.5
50		40	10	**RV0FFI500**	50		0.265	31	16	18	150	110	4.5
63		50	10	**RV0FFI630**	40		0.368	38	18	18	165	125	4.5
75	2 ½	65	10	**RV0FFI750**	20		0.501	44	19	18	185	145	6.0
90		80	10	**RV0FFI900**	15		0.687	51	20	18	200	160	7.0
110		100	10	**RV0FFI910**	10		0.940	61	22	18	220	180	8.0
125		110	10	**RV0FFI920**	6		1.032	69	24	18	230	190	7.0
140	5	125	10	**RV0FFI930**	6		1.335	76	26	18	250	210	7.0
160		140	10	**RV0FFI940**	5		1.835	86	28	18	285	240	7.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com