Data sheet

valid from: 4/5/26



TP Reducing socket PVC-U metric

- (*) with octagon

	d (mm)	d1 (mm)	PN (bar)	Code	SP	Weight (kg)	Z (mm)	E2 (mm)	E1 (mm)	L2 (mm)	L1 (mm)
	20	16	16	**RV0MRI20A**	270	0.010	6	23	28	14	16
	25	20	16	**RV0MRI25B**	200	0.016	6	28	34	16	19
	32	25	16	**RV0MRI32C**	150	0.026	6	34	42	19	22
	40	32	16	**RV0MRI40D**	100	0.053	6	42	51	22	26
	50	40	16	**RV0MRI50E**	60	0.080	6	51	61	26	31
	63	50	16	**RV0MRI63F**	70	0.100	6	61	75	31	38
*	75	63	16	**RV0MRI75G**	50	0.216	4	75	89	38	44
*	90	75	16	**RV0MRI90H**	40	0.347	5	89	106	44	51
*	110	90	16	**RV0MRI91I**	48	0.563	6	106	129	51	61
	125	110	16	**RV0MRI92L**	22	0.736	24	129	145	61	69
	140	110	16	**RV0MRI93L**	18	0.982	25	129	160	61	76
	140	125	16	**RV0MRI93M**	1	1.022	19	145	160	69	76
	160	110	16	**RV0MRI94L**	12	1.200	24	130	181	61	86
	160	140	16	**RV0MRI94N**	9	1.300	8	170	180	76	86
	200	160	16	**RV0MRI96O**	6	2.333	24	184	227	86	106
	225	200	10	**RV0MRI97Q**	4	6.459	10	227	255	106	119

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com